



# TECHNICAL DATA SHEET

## PHTHALOCYANINE VIOLET 19



High Performance Copper Phthalocyanine Pigment




### PRODUCT IDENTIFICATION

|                   |  |
|-------------------|--|
| Chemical Class    | Copper Phthalocyanine                            |
| CI Name           | Pigment Violet 19                                |
| CI No.            | 51319  |
| CAS No.           | 6358-30-1  |
| EINECS / EC No.   | 228-787-0  |
| Molecular Formula | C <sub>32</sub> H <sub>16</sub> CuN <sub>8</sub> |
| Molecular Weight  | 576.06   |
| Appearance        | Bluish Violet Powder                             |
| Shade             | Bluish Violet                                    |

MASSTONE (1%)      TINT SHADE (1%)



### CHEMICAL STRUCTURE



### KEY FEATURES

- High Colour Strength
- Excellent Heat Stability
- Chemical & Solvent Resistance
- Good Opacity
- Reliable Dispersion

### APPLICATIONS



Paints & Coatings



Printing Inks



Plastics & Masterbatch



Rubber & Elastomers



Textile Applications

### TYPICAL PACKAGING



25 Kg / 20 Kg  
Triple Lined HDPE Bags with PE Liner or as per customer request

### PHYSICAL & CHEMICAL PROPERTIES

| PARAMETER                   | SPECIFICATION | TEST METHOD |
|-----------------------------|---------------|-------------|
| Colour (Shade)              | Bluish Violet | Visual      |
| Colour Index                | PV 19         | ISO 787-24  |
| Tinting Strength (%)        | 95 - 105      | ISO 787-24  |
| Heat Resistance             | Up to 300°C   | ISO 787-24  |
| Light Fastness (Full Shade) | 7 - 8         | ISO 105-B02 |
| Weather Fastness            | 5             | ISO 105-B04 |
| Oil Absorption (g/100g)     | 45 - 60       | ISO 787-5   |
| pH (10% Extract)            | 6.0 - 8.0     | ISO 787-9   |
| pH Value                    | 6.0 - 8.0     | ISO 787-9   |
| Bulk Density (g/litre)      | 1.1 - 1.7     | ISO 787-11  |
| Sieve Residue (325 µm) (%)  | Max. 0.5      | ISO 787-7   |

### STORAGE



Store in a cool, dry and well-ventilated area, from direct sunlight and moisture. Keep containers tightly closed when not in use.

### SHELF LIFE



24 months from date of manufacture under proper storage conditions.

### REACH STATUS LEGEND

- REACH Registered** Fully registered under EU REACH.
- Pre-registered / Batch Dependent** Registration or availability depends on batch, volume or specific conditions.
- REACH Supported (Registration in Progress)** Registration process is ongoing for selected products.



**Note:** REACH status may vary by product grade, batch volume, application and regional regulatory requirements. Please refer to product-specific documentation for exact details.

### COMPLIANCE

- REACH Registered
- RoHS Compliant
- Heavy Metals Compliant
- Free from AZO Dyes
- Complies with EN-71-3



**DISCLAIMER:** The information and recommendations contained herein are based on tests believed to be reliable. However, the buyer/user assumes all risk and liability resulting from the use of our products, whether used alone or in combination with other products. It is the user's responsibility to determine the suitability of our products for the user's intended purpose and application.

**NOTE:** Finish technical data provided is typical values and is not intended to be used as a specification.

Version: 1.0  
Date of Issue: May 2024